

Product Safety Information Requirements

| Product Group | Safety Aspects to Consider |
|----------------------|--|
| CabStore Lockers | <ul style="list-style-type: none">Fitting instructions must be followedLoctite is used on all fixingsMaximum Loads MUST be adhered toDo not use fixing points to mount any other equipmentIf fitting a TruckChef microwave must use correct cradle and boltsAny other third party equipment fitted into locker is done so entirely at the users own riskEnsure locker contents are secure and doors fully closed before moving or tilting cab |
| iAM Aerodynamics | <ul style="list-style-type: none">Fitting instructions must be followedLoctite is used on all fixingsMinimum of 3 safety straps (one at the front and 2 at back) must be connected from the spoiler to the mounting baseDo not use fixing points to mount any other equipmentRear adjuster plates to be checked on every serviceIf uprights are present, visual checks for damage and loose fittings should be taken out as part of the drivers daily checksHinge side access via upright must be closed prior to travelDo not use the brackets of the uprights as grab handles unless specifically designed to do soCheck and record the vehicles overall height and display in cab to avoid bridge strikesEnsure rear adjusters are secure before tilting cab |
| TruckChef Microwaves | <ul style="list-style-type: none">Fitting instructions must be followedConnection of any wiring to be done by a trained electrician or auto-technicianPower must be taken from a 40amp fused supplyWe advise all microwaves to be wired following the OEM's bodybuilder guidelines for high amage draw electrical itemsContents removed from microwave may be hotRemove and store cooking plate before travelEnsure microwave door is shut firmly before travelDo not leave microwave unattended in the cab when cookingDo not use the power distributed to the microwave for any other applicancesDo not take apart or try to repair the microwave in any way, this wil void the warrantyKeep vents clear for heat dispertion and air circulationClean microwave regularly to avoid build up of dirt and greaseOnly use "Microwave safe" containersAvoid looking directly into the oven when it is switched onPeople with heart pacemakers must not use this ovenDo not place any metal inside the microwaveNever reheat food more than onceEnsure food is stired part way through cooking and follow the recommended cooking timesEnsure food is piping hot before consumption |
| TreadSafe Catwalks | <ul style="list-style-type: none">Fitting instructions must be followedFor full catwalks, A minimum of 2 safety straps must be installed (one front and one rear) from the catwalk frame to the chassisAs part of the drivers daily checks a visual check should be made on all fixings ensuring they are tight and the catwalk is not loose.Do not use fixing points to mount any other equipment |

When entering the catwalk use three points of contact at all times
Use provided grab handles on the vehicle
Be aware of your surroundings at all times and watch your step
If present, safety information decals must be adhered to
Only enter and leave the catwalk from the "step" side of the vehicle
Never remain on the catwalk longer than required
Keep catwalk free of any debris
Chassis bolts should be checked as part of the vehicle's routine service

MirrorShield Mirror Guards

Fitting instructions must be followed
As part of the driver's daily checks a visual check should be made on all fixings ensuring they are tight and the guard is not loose.
Do not use fixing points to mount any other equipment
If guard is hit, stop the vehicle at the earliest and safest opportunity and check the guard is still secure
If guard is not secure, remove it from the mirror.
Visually check the guards for damage daily.
Do not allow the guard to create an additional blind spot from the vehicle if it becomes loose.
