

strands[®]

-lighting division

WHITE / AMBER
POSITION LIGHT

SIBERIA SR LED BAR *E-APPROVED*



PART NO.	809170	809171	809172	809173	809174
VOLTAGE	9-32V DC	9-32V DC	9-32V DC	9-32V DC	9-32V DC
CONSUMPTION	47W	95W	146W	199W	241W
THEORETICAL LUMEN	4000	8000	12000	16000	19200
ACTUAL LUMEN	3105	5676	8039	9472	11146
1 LUX @	425m	550m	520m	533m	525m
IP-CLASS	IP67/IP69K	IP67/IP69K	IP67/IP69K	IP67/IP69K	IP67/IP69K
BEAM PATTERN	Combo	Combo	Combo	Combo	Combo
POSITION LIGHT	Yes, amber and white	Yes, amber and white	Yes, amber and white	Yes, amber and white	Yes, amber and white
CONNECTION	DT-4	DT-4	DT-4	DT-4	DT-4
CABLE LENGTH	500mm	500mm	500mm	500mm	500mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	300,6mm	555,6mm	813,6mm	1065,6mm	1269,6mm
DEPTH	55,5mm	55,5mm	55,5mm	55,5mm	55,5mm
HEIGHT	45mm	45mm	45mm	45mm	45mm
HEIGHT INCLUDING BRACKET	65mm	65mm	65mm	65mm	65mm
OPERATING TEMPERATURE	-20°C · +45°C	-20°C · +45°C	-20°C · +45°C	-20°C · +45°C	-20°C · +45°C
E-APPROVED	ECE R112	ECE R112	ECE R112	ECE R112	ECE R112
REF	37,5	50	50	50	50
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10