
# SWEDSTUFF.

# SWEDSTUFF.



## **DRIVING LIGHTS**



## LDL-01 / DRIVING LIGHT 9" LED

9-36V DC, 107W, 12 000 theoretical lumen, 10 200 actual lumen, 1 lux @ 469 meters, IP68/IP69K, Combo, White/amber position light, DT-4, 500mm cable, Diameter: 218mm, Depth: 84mm, ECE R112, R7, Ref: 45 Part No. 270787

## PERSONALIZE WITH COLOR

These slim driving lights comes with a modern look, efficient light output and durable quality. Comes with a dual position light – choose color between white and amber. The placement of the four position lights forms an eye-catching pattern that creates character and enhances the overall impression of your vehicle.





## LDL-03 / DRIVING LIGHT 7" LED

9-36V DC, 50W, 5400 theoretical lumen, 4590 actual lumen, 1 lux @ 380m, IP68, Combo, white/amber position light, DT-4, 500 mm cable, Diameter: 180 mm, Depth: 65 mm, ECE R7, R112, Ref: 30 Part No. 270795

## SLIM DESIGN AND HIGH PERFORMANCE

Equipped with LED diodes from world-leading CREE that together with a new reflector gives you a fantastic light experience. The light beam provides width and length in an ideal combination for various driving. Delivers 1 lux at 469 meters. Comes with a dual position light – choose between white and amber.







## LDL-04 / DRIVING LIGHT 9" LED

9-36V DC, 92W, 12 000 theoretical lumen, 9600 actual lumen, 1 lux @ 425m, IP68, Combo, white/amber position light, DT-4, 500 mm cable, Diameter: 218 mm, Depth: 71 mm, ECE R7, R112, Ref: 37,5 Part No. 270796




## POWERFUL STRENGTH AND HIGH QUALITY

The robust appearance enhances the impression and gives your vehicle a modern look.

The light beam is spot, providing a long light that is well suited for long and narrow roads, but it works for anyone looking for a long light beam.





## LDL-05 / DRIVING LIGHT 7" LED

12:24V DC, 66W, 5010 theoretical lumen, 4469 actual lumen, 1 lux @ 572m, IP68, Spot, DT, 500mm cable, Diameter: 178mm, Depth: 75,5/88,8mm, ECE R10 Part No. 270777

#### LDL-06 / DRIVING LIGHT 9'' LED 12·24V DC, 90W, 6560 Theoretical lumen, 6319 Actual lumen, 1 lux @ 678m, IP68, Spot, DT, 500mm cable, Diameter: 228mm, Depth: 80,5/92,1mm, ECE R10 Part No. 270776

NEW



## LDL-02 / DRIVING LIGHT LED


9-36V DC, 79W, 10 000 theoretical lumen, 8500 actual lumen, 1 lux @ 425m, IP68/IP69K, Combo, white/amber position light, DT-4, 500mm cable, LxDxH: 247x92x141mm, ECE R7, R112, Ref: 37,5 Part No. 270789

\* Not availible in Sweden

## MODERN DESIGN AND POWERFUL PERFORMANCE

This is the oval driving light that gives your vehicle a self-confident character, even when it is bright outside. The nicely designed position light comes with dual function, choose between white and amber light.

Immediate start-up and shutdown thanks to LED technology. The light beam mimics and enhances the vehicle's original lighting, giving you a smooth light in the perfect combination of length and width. The lamp delivers impressive 8500 lumens. Suitable for driving in various environments – forest roads, highways and country roads.








## LBL-03 / 7" SR LED BAR

9-35V DC, 14W, 2400 theoretical lumen, 1129 actual lumen, 1 lux @ 304m, IP68/IP69K, Spot, DT, 500mm cable, LxDxH: 177x54,36x40mm, ECE R112, Ref: 25 Part No. 808044








#### LBL-04 / 22" SR LED BAR


9-35V DC, 49W, 8400 theoretical lumen, 3908 actual lumen, 1 lux @ 452m, IP68/IP69K, Combo, DT, 500mm cable, LxDxH: 522x54,36x40mm, ECE R112, Ref: 50 Part No. 808045





#### LBL-05 / 32" SR LED BAR

9-35V DC, 77W, 13 200 theoretical lumen, 5409 actual lumen, 1 lux @ 465m, IP68/IP69K, Combo, ATP, 500mm cable, LxDxH: 798x54,36x40mm, ECE R112, Ref: 50 Part No. 808046





## AN EXTREME UPGRADE


These SR and DR LED bars blends in perfectly with your vehicle and is an extreme upgrade from the traditional, robust models that dominates the market. Slim, dark and sophisticated. The lens goes from edge to edge with an extremely thin frame.

Available in both single-row (SR) and double-row (DR) versions. All models are E-approved.



## LBL-08 / 32" DR LED BAR


9-35V DC, 113W, 24000 theoretical lumen, 7843 actual lumen, 1 lux @ 485m, IP68/IP69K, Combo, ATP, 1000mm cable, LxDxH: 815,6x67,3x70mm, ECE R112, Ref: 50 Part No. 808049



0.255

2319b

30m 20m 10m 0m -10n -20n -30r





LBL-06 / 8" DR LED BAR

9-35V DC, 24W, 4800 theoretical lumen, 2068 actual lumen, 1 lux @ 318m, IP68/ IP69K, Combo, DT, 500mm cable, LxDxH: 203,6x67,3x70mm, ECE R112, Ref: 25 Part No. 808047



## LBL-07 / 22" DR LED BAR

9-35V DC, 83W, 16 000 theoretical lumen, 4860 actual lumen, 1 lux @ 482m, IP68/IP69K, Combo, DT, 1000mm cable, LxDxH: 560,6x67,3x70mm, ECE R112, Ref: 45 Part No. 808048








## LBL-11 / 22" DRC LED BAR


9-35V DC, 79W, 16 000 theoretical lumen, 5884 actual lumen, 1 lux @ 408m, IP68/IP69K, Combo, DT, 1000mm cable, LxDxH: 562,9x78,63x70mm, ECE R112, Ref: 40 Part No. 808052





## LBL-12 / 32" DRC LED BAR

9-35V DC, 247W, 24 000 theoretical lumen, 12 264 actual lumen, 1 lux @ 614m, IP68/IP69K, Combo, ATP, 1000mm cable, LxDxH: 814,9x78,63x70mm Part No. 808053





## **OPTIMIZED LIGHT BEAM**


Curved shape, appealing from all angles. SRC and DRC LED bars offers an optimized light beam that provides maximum width, without losing length. Available in both singlerow (SRC) and double-row (DRC) versions.

The rounded design fits perfectly on vehicles with a curved front.



## LBL-09 / 22" SRC LED BAR


9-35V DC, 24W, 4800 theoretical lumen, 2068 actual lumen, 1 lux @ 318m, IP68/IP69K, Combo, DT, 500mm cable, LxDxH: 203,6x67,3x70mm, ECE R112, Ref: 25 Part No. 808050





## LBL-10 / 32" SRC LED BAR

9-35V DC, 83W, 16000 theoretical lumen, 4860 actual lumen, 1 lux @ 482m, IP68/IP69K, Combo, DT, 1000mm cable, Polycarbonate lens, LxDxH: 560,6x67,3x70mm, ECE R112, Ref: 45 Part No. 808051





## SOPHISTICATED DESIGN

The light beam of LBL-01 and LBL-02 is perfectly optimized, providing both a long light on the road and a wide light light in the ditch edges.

The black-lacquered aluminum housing and the polycarbonate lens makes it impact-resistant and immune to scratches. E-approved, which makes it legal to mount on the vehicle as a driving light.



**SWEDSTUFF** 

## LBL-01 / 20" LED BAR


12-24V DC, 90W, 7560 theoretical lumen, 4690 actual lumen, 1 lux @ 450m, IP67, Combo, DT, 300mm cable, LxDxH: 535x68x32,5mm, ECE R112, Ref: 37,5, ECE R10 Part No. 808042

## LBL-02 / 20" LED BAR

12-24V DC, 180W, 15 120 theoretical lumen, 9859 actual lumen, 1 lux @ 650m, IP67, Combo, DT, 300mm cable, LxDxH: 550x75x56,6mm, ECE R112, Ref: 37,5, ECE R10 Part No. 808043









### LBL-19 / 22" LED BAR

12-24V DC, 120W, 8400 theoretical lumen, 4400 actual lumen, IP67, combo, LxDxH: 560x88x82mm Part No. 808037




## **OPTIMIZED LIGHT BEAM**

This LED bar comes with a slim, modern design. It is developed with the optimal lighting experience in focus. The light beam creates the perfect balance and gives you a safe driving experience with light where you need it most.



## LBL-18 / 22" LED BAR


12-24V DC, 120W, 8000 theoretical lumen, 7240 actual lumen, IP68, combo, LxDxH: 560x88,66x84mm, ECE R112, Ref: 30 Part No. 809210





#### LBL-17 / 21" LED BAR

12-30V DC, 45W, 4050 theoretical lumen, 2530 actual lumen, IP69K, combo, DT-connector, LxDxH: 524x59x52mm, ECE R112, Ref: 25 Part No. 808033






## Available in five different lengths, up to 20 000 lumen – Select the one that fits you and your vehicle best!



**O'O'O'O'O'O'O'O'O'** 

### LBL-20 / 21" LED BAR


12:24V DC, 90W, 9000 theoretical lumen, 5188 actual lumen, IP67, Combo, LxDxH: 539x86x80mm, ECE R112, Ref: 37,5 Part No. 808036





## LBL-21 / 28" LED BAR

12-24V DC, 120W, 10 800 theoretical lumen, 6799 actual lumen, IP67, combo, LxDxH: 703,6x86x80mm Part No. 808038



8m 149lx 5m

25m

2m 0m -2m -5m




#### LBL-22 / 34" LED BAR 12-24V DC, 150W, 13500 theoretical lumen, 8498 actual lumen, IP67, combo, LxDxH: 868,6x86x80mm Part No. 808039




#### LBL-23 / 41" LED BAR

12-24V DC, 180W, 16200 theoretical lumen, 10080 actual lumen, IP67, combo, LxDxH: 1033,6x86x80mm Part No. 808040




#### LBL-24 / 54" LED BAR

12-24V DC, 240W, 20000 theoretical lumen, 13440 actual lumen, IP67, combo, LxDxH: 1363,6x86x80mm Part No. 808041











## SMALL, BUT POWERFUL

Shock-resistant work light that fits most types of vehicles. Lots of illumination, despite the small size. Classic design with cut-corners that give character to the overall impression. Suitable as extra lighting for a tractor, loader, car, boat, truck or excavator.

## LWL-01 / WORK LIGHT LED

9-32V DC, 31W, 2750 theoretical lumen, 2200 actual lumen, IP67/IP69K, 520mm cable, LxDxH: 70,4x41x70,4mm Part No. 808010










## LWL-06 / WORK LIGHT LED

12-24V DC, 27W, 1800 theoretical lumen, 1600 actual lumen, IP67, LxDxH: 110x55x110mm Part No. 808003

LWL-05 / WORK LIGHT LED 12·24V DC, 48W, 3300 theoretical lumen, 2350 actual lumen, IP67, LxDxH: 115x62x115mm Part No. 808002




## **WORK LIGHTS**





## LWL-15 / WORK LIGHT LED

12-24V DC, 18W, 1100 theoretical lumen, 850 actual lumen, IP67, LxDxH: 160x70x45mm Part No. 808150



## **CLASSIC DESIGN**

Shock-resistant work light that fits most types of vehicles. Classic design with cut-corners that give character to the overall impression. Suitable as extra lighting for a tractor, loader, car, boat, truck or excavator.



## LWL-02 / WORK LIGHT LED

9-32V DC, 64W, 6187 theoretical lumen, 5200 actual lumen, IP67/IP69K, 520mm cable, LxDxH: 101x45x101mm Part No. 808011



## **WORK LIGHTS**

## NEW




## COMPACT SOLUTION

The light beam combinates width and length – an optimized solution.

Discreet and neat perfect for use where larger lighting does not fit. A really powerful lamp that should not be underestimated for its small size.

LWL-04 / WORK LIGHT LED 9-35V DC, 41W, 3317 theoretical lumen, 1600 actual lumen, IP68/IP69K, Connection: DT, 500mm cable, LxDxH: 81x67,5x75mm Part No. 808054




1b

90m

0,4lx

140m





## LWL-09 / WORK LIGHT LED

12-24V DC, 15W, 1500 theoretical lumen, 1297 actual lumen, IP69K, LxDxH: 109x35x109mm Part No. 808006 LWL-10 / WORK LIGHT LED 12·24V DC, 9W, 1000 theoretical lumen, 894 actual lumen, IP69K, LxDxH: 108x35x108mm Part No. 808007




## **WORK LIGHTS**




LWL-11 / WORK LIGHT LED 12-24V DC, 18W, 2000 theoretical lumen, 1671 actual lumen, IP69K, DT-connector, LxDxH: 109x40x109mm Part No. 808008



LWL-17 / WORK LIGHT BLUE LED 10-80V DC, 11W, IP67, ØxD: 104x74mm Part No. 808009



Rechargeable





## LWL-08 / WORK LIGHT LED

12-24V DC, 12W, 960 theoretical lumen, 490 actual lumen, IP69K, LxDxH: 159x38x45mm Part No. 808005

## LWL-16 / WORK LIGHT LED

12·24V DC, 18W, 1296 theoretical lumen, 648 actual lumen, IP65, LxDxH: 105x105x153mm, height inc. handle 201mm Part No. TD90010





## LWL-05 / WARNING LIGHT LED

12-24V DC, 27W, 7 patterns, IP67, amber lens, white LED, 300mm cable, ØxH: 112x46mm, ECE R65 Part No. 808097 Surface mounting

## 26 different flash patterns



LWL-09 / WARNING LIGHT LED 12-24V DC, 12W, 26 patterns, IP67, clear lens, amber LED, 400mm cable, LxDxH: 74x32x74mm, ECE R65 Part No. 800221



HWL-01 / WARNING LIGHT HALOGEN 12-24V DC, 55W, 1 pattern, IP56,

amber lens, ØxH: 140x210mm Part No. 808091 Surface mounting, H1



HWL-02 / WARNING LIGHT HALOGEN

12-24V DC, 55W, 1 pattern, IP56, amber lens, ØxH: 128x245mm, ECE R65 Part No. 808092 Pole mounting, H1



LWL-04 / WARNING LIGHT LED 10-110V DC, 9W, 1 pattern, IP56, amber lens, ØxH: 100x130mm Part No. 808096 Surface mounting





## LWL-01 / WARNING LIGHT LED

12-24V DC, 8W, 3 patterns, IP55, amber lens, white LED, ØxH: 140x125mm Part No. 808066 Surface mounting

### LWL-03 / WARNING LIGHT LED

12-24V DC, 8W, 3 patterns, IP55, amber lens, white LED, ØxH: 128x140mm Part No. 808068 Magnet + cigg plug



LWL-11 / DUO LIGHTHEAD LED

12-24V DC, 2x10W, 23 patterns, IP67, clear lens, amber LED, LxDxH: 27x39x24mm, ECE R65 Part No. 850122HP-A



## LWL-06 / WARNING LIGHT LED

12:24V DC, 9W, 3 flash patterns, IP66, amber lens, white LED, 3100mm cable with cigg plug (on off/switch), ØxH: 120x43mm Part No. 808098





#### LWL-08 / WARNING LIGHT BAR LED

12-24V DC, 30W, 8 patterns, IP56, clear lens, amber LED, LxDxH: 416x80x80mm, ECE R65 Part No. 808095





## LWL-10 / WARNING LIGHT PUCK LED

9 patterns, IP66, clear lens, red LED, ØxD: 105x35mm. With battery – up to 100h, reach up to 500 meters Part No. 808101

LWL-14 / LIGHTHEAD LED 12-24V DC, 3W, 14 patterns, IP65, clear lens, amber LED, LxDxH: 115x30x34mm, ECE R65 Part No. 808090-A



## LWL-12 / LIGHTHEAD LED

12-24V DC, 12W, 26 patterns, IP67, clear lens, amber LED, 400mm cable, LxDxH: 98x6,6x31mm, ECE R65 Part No. 850124HP-A







LTL-01 / WIRELESS TAIL LIGHT KIT LED

12V DC, Tail light, brake light, dynamic indicator, number plate light, IP67, LxDxH: 110x103x40mm, ECE R4, R6, R7, ECE R10 Part No. 800720 Part No. 800721 / 24V DC transmitter for LTL-01

The kit includes: right + left lamp, transmitter 7-pol and cig plug charger. Magnet base = no installation needed.





## HYTL-01 / 3 FUNC. TAIL LIGHT HYBRID

Hybrid, 3 functions: LED: tail, brake. Bulb: indicator. 12-24V DC, IP54, ECE R6, R7, 121x101x57mm Part No. 808815



LTL-02 / 3 FUNC. TAIL LIGHT LED

LED, 3 functions: tail, brake, indicator. 12-24V DC, IP68, ECE R6, R7, 120x100x55mm Part No. 800050-S



**HYTL-02 / 5 FUNC. TAIL LIGHT** *HYBRID* Hybrid, 5 functions: LED: tail, brake. Bulb: indicator, fog,

reverse. 12-24V DC, IP55, ECE R3, R6, R7, R23, R38, R91, LxDxH: 464x130x97,5mm Part No. 870010



**HYTL-02 / 3 FUNC. TAIL LIGHT** *HYBRID* Hybrid, 3 functions: LED: tail, brake. Bulb: indicator.

12-24V DC, IP54, ECE R6, R7, LxDxH: 200x70x62mm Part No. 808816



## **SIDE MARKERS / POSITION LIGHTS**



## DOUBLE BURNER HALOGEN

A really popular styling lamp that is usually mounted in pairs in the front of the truck.

12-24V DC, 2xBA15s (not included), LxDxH: 130x40x60mm, CC: 110mm Part No. 800070 HPL-01 / Amber glass, ECE R91 Part No. 800071 HPL-02 / Clear glass



DOUBLE BURNER *LED* 24V DC, 0,7W, LxDxH: 126,6x39,2x55,1mm CC: 109mm Part No. 800072 LPL-15 / White Part No. 800073 LPL-16 / Amber



## **POSITION LIGHT** LED

12-24V DC, IP68, ECE R7, LxDxH: 80,5x14x60mm, CC: 67mm Part No. 808809 LPL-09 / Red Part No. 808810 LPL-10 / White



#### SHORT RUBBER ARM LED

LED, 12-24V DC, IP68, ECE R7, LxDxH: 78x71x59mm Part No. 808811 LPL-11 / Left Part No. 808812 LPL-12 / Right



LONG RUBBER ARM *LED* LED, 12-24V DC, IP68, ECE R7, LxDxH: 216x59x49mm Part No. 808813 LPL-13 / Left Part No. 808814 LPL-14 / Right





## SIDE MARKER / POSITION LIGHT LED

These lamps can be mounted in vertical or horizontal position.

12-24V DC, IP68, LxDxH: 105,4x11,8x45/67,5mm, CC: 30mm Part No. 808800 LSML-01 / Amber, ECE R91, R3 Part No. 808801 LPL-03 / Red, ECE R7, R3 Part No. 808802 LPL-04 / White, ECE R7, R3



## SIDE MARKER / POSITION LIGHT LED

12-24V DC, IP68, LxDxH: 98x25x31,5mm, CC: 30mm Part No. 808807 LSML-02 / Amber, ECE R91, R3 Part No. 808805 LPL-06 / Red, ECE R7, R3 Part No. 808803 LPL-05 / White, ECE R7, R3



## SIDE MARKER / POSITION LIGHT LED

12-24V DC, IP68, LxDxH: 98x25x31,5/58,5mm, CC: 30mm Part No. 808808 LSML-03 / Amber, ECE R91, R3 Part No. 808806 LPL-08 / Red, ECE R7, R3 Part No. 808804 LPL-07 / White, ECE R7, R3



## **REFLECTOR / LED CONVERSION KIT**




## **RS-08 / REFLECTOR**

Diameter: 74mm, M6, depth: 12mm, white plate, ECE R3 Part No. 880029-S



#### RS-01 / REFLECTOR 135x155mm, screw on the back, cc: 70mm, rounded corners, ECE R3 Part No. 818838



#### REFLECTOR

4-pack, 96x42mm, with tape, ECE R3 Part No. 818856-4 RS-05 / White Part No. 818857-4 RS-06 / Red Part No. 818858-4 RS-07 / Amber



REFLECTOR 4-pack, 66mm, 5,2mm screw hole, ECE R3 Part No. 818850-4 RS-02 / White Part No. 818851-4 RS-03 / Red

Part No. 818852-4 RS-04 / Amber



## LCK-01 / LED CONVERSION KIT H4

12-24V DC, 24W, 3200 theoretical lumen, 2800 actual lumen, 6500K, IP67, Diameter: 23mm, Height: 82,5mm Part No. 808832



## LCK-02 / LED CONVERSION KIT H7

12-24V DC, 24W, 3200 theoretical lumen, 2800 actual lumen, 6500K, IP67, Diameter: 26,8mm, Height: 68,8mm Part No. 808833



## **DVR CAMERAS**

SUCTION CUP

## **Full HD**





FULL HD CAR DVR 1080P

4=2.0/f=3.2mm

DIGITAL CAMCORDE

DVRC-02 / DVR DIGITAL CAMERA 1,3 MPX, 2,5" TFT LCD display, USB + cigg plug charger, SD-card included, full HD, 12-24V DC, 170 degrees angle, VGA 30 FPS Part No. ST650-SD



Navigation

Audio 4

Tel

System

+46 (0)320-450 450 info@swedstuff.com | www.swedstuff.com



7"323030"188351"

With reservation for misprints and possible changes.